

MaxxLube® RW-100 Sanforizing Lubricant and Softener

MaxxLube RW-100 is a stable water soluble non-ionic Sanforizing lubricant and softener. MaxxLube RW-100 has

TYPICAL PROPERTIES

Appearance	Amber Liquid
Solids, %	95
Ionic Nature	Non-ionic
Viscosity, cPs	300
pH, (1% solution @ 25°C)	7

Application and Use:

- Excellent Rewetting Properties (Especially useful in compressive shrinkage processing)
- M Odor-free and discoloration Resistant Properties
- Excellent Lubrication and Softening Properties
- Improved Sewability of Treated Goods

MaxxLube RW-100 is readily diluted with warm water. Conventional finishing equipment may be used in applying MaxxLube RW-100 to fabrics. The product is applied to fabric and then dried in the normal manner. Recommended dosage of 1-1.5% owg added to the pad bath.

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.