



MaxxSeal® 200 Styrene Acrylic Copolymer Emulsion

MaxxSeal 200 is a firm styrene acrylic co-polymer emulsion with excellent water resistance and aging properties. It is used in soil/aggregate stabilization dust control applications. **MaxxSeal 200** is used where excellent binding properties are needed in tying up aggregate in the road base or in preventing airborne dust. Use of **MaxxSeal 200** allows mines, construction sites and dusty areas to avoid the dangers associated with fines.

TYPICAL PROPERTIES

Type	Styrene Acrylic Emulsion Polymer
Total Solids	50%
Weight per Gallon	8.80
T _g	+18°C
Specific Gravity (Latex)	1.06
Specific Gravity (Solids)	1.15
pH	2.5
Viscosity	<800 cps (RV 2 @ 60 rpm)
Surfactant Charge	Anionic

PERFORMANCE FEATURES

Outstanding Water Resistance – High Tensile Strength – Environmentally Safe – Alkali Resistant
Very Shear Stable – Excellent Aging Properties

SUGGESTED USES

Soil Stabilization – Road Construction

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.