



Maxxacryl SA-2180 Styrene Acrylic Emulsion Polymer

Maxxacryl SA-2180 is a firm styrene acrylic emulsion with excellent water resistance and aging properties. Coatings containing **Maxxacryl SA-2180** yields a hard water resistant finish that has excellent resistance to abrasion and alkali. **Maxxacryl SA-2180** is compatible with most pigments, fillers and formulating additives.

TYPICAL PROPERTIES

Type	Styrene Acrylic Emulsion Polymer
Total Solids	50%
Weight per Gallon	8.8
T _g	+18°C
Specific Gravity - Latex	1.06
Specific Gravity – Solids	1.15
pH	2.5
Viscosity	<800 cps (RV2 @ 60 rpm)
Surfactant Charge	Anionic

Performance Features

Hi Tensile Strength – Alkali Resistance - Outstanding Water Resistance – Sheer Stable - Excellent Aging Properties

Suggested Use

Bonding Adhesives – Vertical Wall Coverings – Masonry Coatings – Water Proofing Coatings – Mastics – Ceramic Tile Mastics

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.