



## PermaPel® 6073 Styrene Acrylic Emulsion Polymer

**PermaPel 6073** emulsion is a very firm, formaldehyde-free, carboxylated, styrene-acrylic copolymer emulsion. Films of **PermaPel 6073** emulsion are very firm and exhibit excellent resistance to discoloration. These films are also characterized by their superior water repellency and adhesion to low energy surfaces. This polymer should be used where a firm film, water resistance, and superior aging characteristics are required.

### TYPICAL PROPERTIES

Type	Styrene Acrylic
Total Solids	50%
Weight per Gallon	8.8
T <sub>g</sub>	+30°C
Specific Gravity (Latex)	1.06
Specific Gravity (Solids)	1.15

### PERFORMANCE FEATURES

Water Repellant - Excellent Weather Resistance - Strong, firm film - Compatibility with large range of pigments and fillers – Adhesion to low energy surfaces

### SUGGESTED USES

Industrial Coatings - Vertical Wall Coatings – Primers – Adhesives

### Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

### McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.