



PermaPel SRZ6019 Styrene Acrylic Emulsion Polymer

PermaPel SRZ6019 emulsion is a very soft, non-tacky binder that is a self-crosslinking, carboxylated, styrene-acrylic copolymer emulsion. Films of **PermaPel SRZ6019** emulsion are very soft and exhibit excellent resistance to discoloration. These films are also characterized by their superior water repellency. This polymer should be used where flexibility, water repellency, wash durability and superior aging characteristics are required. **PermaPel SRZ6019** is a McTron polymer that incorporates our wash durable specialty monomer technology with the addition of a non-formaldehyde generating crosslinking system designed to eliminate crocking of denim and other dyed fabrics. **PermaPel SRZ6019** also exhibits exceptional adhesion properties to low energy surfaces.

TYPICAL PROPERTIES

Type	Styrene Acrylic
Total Solids	50%
T _g	-19°C
pH	8.5
Viscosity	<2000 cPs

PERFORMANCE FEATURES

Water Repellant - Excellent Weather Resistance - Strong, Flexible Film - Compatibility with large range of pigments and fillers, Ultra low-formaldehyde, Durable to many washes, Heat Resistant, Solvent Resistant

SUGGESTED USES

Textile Coatings – Caulks - Mastics

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.