



**MaxxCoat® E-132  
Paraffin Wax**

**MaxxCoat E-132** is a concentrated general-purpose water-based treatment for paper and corrugated board. It imparts a high level of water repellence. **MaxxCoat E-132** should be diluted with water before use to a level that satisfies the end use requirement. Typical dilution with water is 1:1. The product meets FDA requirements set forth in 21 CFR 176.170 and 176.180, subject to the finished food-contact article meeting the extractive limitations under the intended use. Blade or rod coaters can apply **MaxxCoat E-132**, preferably at the wet end of the corrugator. It is also sprayable and the treated board is gluable with most cold set and hot melt adhesives. It is also printable with most flexography inks at a 1:1 dilution.

**TYPICAL PROPERTIES**

Appearance	White Emulsion
pH	10-11
Viscosity, EZ#2	15-30 Seconds
Specific Gravity	0.95
Freeze/Thaw	Unstable

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

**McTron Technologies LLC Guarantee**

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.

