








MaxxLube® HDPE-2540 Oxidized High Density Polyethylene Emulsion

MaxxLube HDPE-2540 is a high-density oxidized polyethylene micro emulsion that provides sewing lubricity, tear-strength protection, abrasion resistance, and sanforizing lubricity to a variety of textile fabrics. It can be added to a number of coating formulations to improve abrasion, release, slip, and prevent adhesion.

TYPICAL PROPERTIES

Appearance	Tan Translucent Liquid
Viscosity, 25°C; 2/100 LVT	<120
pH	9-11.5
Solis,	40

Performance Features:

-  **Excellent sewing and napping lubricant**
-  **Abrasion resistant lubricant**
-  **Compatible with many polymers**
-  **Retains hardness at higher temperatures**
-  **Provides surface lubricity, slip and release properties**

Markets:

-  **Textiles**
-  **Paper**
-  **Coatings**
-  **Adhesives**

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.