



MaxxBond SB-115X54

Carboxylated Styrene Butadiene Latex

MaxxBond SB-115X54 is a binder for coated paper and paperboard applications as well as improved wet strength in primary pre-coat and secondary adhesive formulations for carpet. **MaxxBond SB-115X54** binder is accepting of many types of inorganic fillers, including finer grind ATH types and recycled fillers in both standard and frothed applications

TYPICAL PROPERTIES

Type	Carboxylated Styrene Butadiene
Appearance	White Aqueous Liquid
Total Solids	54%
pH	7.5
Emulsifier	Anionic
Viscosity, <i>LVT#2@ 60 rpm, 25°C</i>	<300 cps
Tg	15°C

Performance Features

Provides Improved wet strength Usable in both primary pre-coat and secondary adhesive formulations, Excellent colloidal stability with improved frothed rheology properties

Suggested Use

Binder: Packaging Paper and Board, Communication papers, Primer coating: Binder for carpets

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.