



**Maxxbreak® OB-946 NS**  
**Industrial Water-Based Defoamer**

**MaxxBreak OB-946 NS** is a completely emulsifiable non-silicone defoamer for difficult problems requiring “fisheye-free” properties. Add directly to system being defoamed, either as received or by first making water dilute emulsions of **MaxxBreak OB-946 NS**. Can be metered or added as one of the formula ingredients. Normally 0.05 to 0.2% of **MaxxBreak OB-946 NS** is an effective quantity to add for most difficult foaming systems. **MaxxBreak OB-946 NS** is a very long lasting defoamer and will prevent foam formation and air entrapment on aged systems. In coatings and paints it serves not only as a highly effective defoamer, but it also improves coating leveling.

**TYPICAL PROPERTIES**

Appearance	Light Cream Liquid
Ionic Charge	Nonionic
pH, 2%	6.6
Active Solids, %	100
Weight per Gallon	~7.3 pounds
Solubility	Dispersible

**PERFORMANCE FEATURES**

Non-Silicone, Concentrated, Versatile, Dilutable

**SUGGESTED USES**

Paints, Pulp and Paper Mill Systems, Chemical Cooking & Bleaching, Distillations, Microbiological Fermentations, Monomer Stripping, Fiberboard, Wastewater

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

**McTron Technologies LLC Guarantee**

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.