



MaxxBreak OS-146

Organo-Silicone Emulsion Antifoam

MaxxBreak OS-146 is a general-purpose antifoam/defoamer. It is highly effective in systems of SBR, PVA, PVC, polyethylene and miscellaneous copolymers. **MaxxBreak OS-146** can be added as received or dispersed in water prior to use. In paint manufacturing, it is usually advantageous to divide the defoamer addition into two parts. One part is added to the pigment prior to grinding; the second part is added to the let-down portion of the paint. Normally 2 to 4 pounds of **MaxxBreak OS-146** is effective for 100 gallons of paint.

TYPICAL PROPERTIES

Appearance	Cream colored liquid
Ionic Nature	Nonionic/Anionic
Active Ingredients, %	98
pH, 2%	6.8
Viscosity	Medium Viscosity Fluid
Weight per Gallon, lbs.	7.8
Solubility	Dispersible in water
Flash Point, °F	>300

PERFORMANCE FEATURES

Extremely effective antifoam, SBR, PVAc, Polyethylene and Polyethylene Emulsions,

SUGGESTED USES

Paints, Adhesives, Coatings

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.