



MaxxSeal® 100 Vinyl Acrylic Copolymer Emulsion

MaxxSeal 100 is a vinyl acrylic co-polymer emulsion used in soil and aggregate stabilization. **MaxxSeal 100** dries to a flexible yet hard state and has excellent durability. It is non hazardous and has no environmental impact. **MaxxSeal 100** dries clear and preserves the natural look and color of the native soil.

TYPICAL PROPERTIES

Type	Vinyl Acrylic Emulsion Polymer
Total Solids	55%
Weight per Gallon	9.05
T _g	+7°C
MFFT	<0°C
Particle Size	0.47 microns
Specific Gravity (Latex)	1.06
Specific Gravity (Solids)	1.15
pH	4-5
Viscosity	<1000 cps (#3 @ 100 rpm)
Surfactant Charge	Non Ionic/Anionic
Freeze-thaw Stability	Do Not Freeze
Bulking Value	0.1105 gal./lb.

PERFORMANCE FEATURES

Economical - Flexible – Environmentally Safe – Very Good Consistency – Dries Clear

SUGGESTED USES

Soil and Aggregate Stabilization

Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.