



## Maxxacryl LP-45 Acrylic Emulsion Polymer

**Maxxacryl LP-45** is heat reactive carboxylated general-purpose soft acrylic latex emulsion. It has use as a flock adhesive, print binder and in applications where solvent resistance, water resistance and durability are desired.

### TYPICAL PROPERTIES

Type	Acrylic Emulsion Polymer
Total Solids	45%
Density @ 25°C (lb./gal.)	8.0 – 9.0
T <sub>g</sub>	11°C
pH	7.5
Viscosity	<100 cps

### Performance Features

Heat Reactive – Water & Solvent Resistant - Soft

### Suggested Use

Coatings – Print Binder – Flock Adhesives – General Purpose

### Let MCTRON Technologies raise your expectations.

McTron Technologies, LLC Technical Support Team is available to provide assistance with the formulation of all our products to optimally suit your specific needs.

### McTron Technologies LLC Guarantee

If any product is defective in workmanship or materials, McTron Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. McTron Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.