



MaxxBreak® OS-578B Organo-Silicone Emulsion

PRODUCT DESCRIPTION

MaxxBreak OS-578B is a nonionic emulsion of organo-silicone compounded with antifoam ingredients. Applications include cutting oils, water-based inks, paints, detergent solutions, PVA solutions, starch solutions adhesives, antifreeze, insecticides, textiles and many other industrial water-based systems. MaxxBreak OS-578 can be added directly to the system being defoamed or can be pre-diluted with equal volume of water to provide easier additions.

TYPICAL PROPERTIES

Appearance	White Liquid
Ionic Nature	Non-Ionic
pH, 2% Solution	7.5
Specific Gravity, @25C	1.0
Freeze/Thaw Stability	Excellent
Water Dispersibility	1%
Viscosity, CPS@25C	Thixotropic Liquid
Flash Point	None

MaxxBreak® OS-578B has excellent shelf life of 12 months. It should be stored in cool conditions. Refer to the **MaxxBreak® OS-578B** SDS for further handling information.

Benefits & Features

- ▶ **Excellent Versatility**
- ▶ **Excellent Defoaming**
- ▶ **Excellent Shelf Life**
- ▶ **Economical**
- ▶ **Water Dispersible**

APPLICATION & DOSAGES

MaxxBreak® OS-578B can be added to the system either just prior to or at the foam forming area. Normally 0.10 to 0.50% dosages will control most foam systems. MaxxBreak OS-578 is effective over a wide pH range.

Let MCTRON Raise Your Expectations...

MCTRON's Technical Support Team is available to assist with the formulation of all our products to optimally suit your specific production needs and manufacturing environment.

MCTRON Technologies Guarantee

If any product is defective in workmanship or materials, MCTRON Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. MCTRON Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.