

MaxxBreak OS-84 C

Organo-Silicone Defoamer



PRODUCT DESCRIPTION

MaxxBreak OS-84 C is a concentrated 100% active organo-silicone defoamer that is effective in combatting micro-foam in paints and coatings. It is suitable for both clear and pigmented formulas.

TYPICAL PROPERTIES	
Appearance	Slightly hazy liquid
Ionic Nature	Nonionic
Solubility	Insoluble
Percent Active	100
Flash Point	>212F

HANDLING & STORAGE

The manufacture of this product is within the scope of the ISO 9001 Quality Management System. **MaxxBreak® OS-84 C** is stable for up to one year. Please see the Material Safety Data Sheet before handling this product.

Benefits & Features

- ▶ **Highly effective in grind phase**
- ▶ **Non-Ionic**
- ▶ **High Shear Recommended**

APPLICATION & DOSAGES

MaxxBreak OS-84 C can be pre-diluted or added as received. It is highly effective when used in the grind phase and can be used in the let down phase with sufficient shear. A starting dosage of 0.25% is recommended.

Let MCTRON Raise Your Expectations...

MCTRON's Technical Support Team is available to assist with the formulation of all our products to optimally suit your specific production needs and manufacturing environment.

MCTRON Technologies Guarantee

If any product is defective in workmanship or materials, MCTRON Technologies, LLC will replace the product, or refund the full purchase price. This warranty is in place of all other warrants, expressed or implied, and all implied warrants of a product for an intended use shall be solely up to the user. MCTRON Technologies, LLC assumes no liability for consequential damages. Its liability shall in no event exceed the purchase price of materials supplied by it.